HAULOTTE ARTICULATED WORK PLATFORMS HA16PE DEUTZ F3L-1011F

Check every 10 hours, change every 1000 hours/ 12 months



(2006-2012)

Change every 50 hours

	CLIMATE Mediterranean			
	Mediterranean			
Check every 10 hours, change every 1000 hours/ 12 months				
	CLIMATE			
	Moderate			
DUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
ar 0W-40	Agridiesel CRD+ 15W-40			
	DUCT RECOMMENDATION 2			

REDUCTION UNIT Capacity: 0,7 liter (each)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		
Check every 10 hours, change every 500 hours/ 6 months			

USE
Initial service

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

CLIMATE
Moderate

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

Check every 10 hours, change every 1000 hours/ 12 months

PRODUCT RECOMMENDATION

HAULOTTE ARTICULATED WORK PLATFORMS HA16PE DEUTZ F3L-1011F



(2006-2012)

inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.