

HAULOTTE TELESCOPIC PLATFORMS

H28TJ+ PERKINS 804D-33T (2008-2014)



ENGINE Perkins 804D-33T

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Check every 10 hours, change every 500 hours/ 12 months

REDUCTION UNIT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 250 hours/ 12 months

SLEWING GEARBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 500 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 140 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 10 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	

Check every 10 hours, change every 1000 hours/ 12 months

HAULOTTE TELESCOPIC PLATFORMS

H28TJ+ PERKINS 804D-33T (2008-2014)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 24 months/ 3000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.