

# HITACHI TRACKED CRANES SCX 1200-2

## (2008 AND AFTER)

**ENGINE** Isuzu 6HK1X

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W****HYDRAULIC SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

PRODUCT RECOMMENDATION 2

**Perlus H 46***Check every 8 hours, change every 2000 hours*

USE	CLIMATE
Clamshell operation	Moderate

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

PRODUCT RECOMMENDATION 2

**Perlus H 46***Check every 8 hours, change every 1500 hours***GREASE POINTS/NIPPLES BOOM FOOT PIN**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

# HITACHI TRACKED CRANES SCX 1200-2

## (2008 AND AFTER)



### GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

### GREASE POINTS/NIPPLES SWING BEARING

We are unable to give a standard recommendation for this component. Please contact our service department.

### DERRICKING UNIT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

### FUEL INJECTION PUMPS

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 40</b>		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

### HOISTING MECHANISM FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

# HITACHI TRACKED CRANES SCX 1200-2

## (2008 AND AFTER)



### HOISTING MECHANISM REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

### SWING REDUCTION UNIT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

### TRAVEL REDUCTION UNIT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*