

HITACHI WHEELED EXCAVATORS EX 100WD

**ENGINE**

Capacity: 20 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W**DIFFERENTIAL FRONT**

Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90**DIFFERENTIAL REAR**

Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90**HUB REDUCTIONS**

Capacity: 3 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

HITACHI WHEELED EXCAVATORS EX 100WD



HYDRAULIC SYSTEM

Capacity: 120 liter (Hydraulic tank), Capacity: 133 liter (Total)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

GREASE POINTS/NIPPLES FRONT JOINT PINS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

GREASE POINTS/NIPPLES SWING BEARING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

GREASE POINTS/NIPPLES SWING INTERNAL GEAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 20 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

HITACHI WHEELED EXCAVATORS EX 100WD


SWING REDUCTION UNIT

Capacity: 3,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.