PRODUCT RECOMMENDATION

# HITACHI TRACKED EXCAVATORS EX EX 120 (1994-1994)

## ENGINE
Capacity: 15 liter

| USE | CLIMATE |
|---|---|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Multifleet SCD 40** | | |

*Check every 8 hours, change every 250 hours*

| USE | CLIMATE |
|---|---|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Multifleet SCD 30** | | |

*Check every 8 hours, change every 250 hours*

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Dieselfleet CD+ 15W-40** | **Multifleet SHPD 15W-40** | |

*Check every 8 hours, change every 250 hours*

| USE | CLIMATE |
|---|---|
| Normal | Arctic |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Multifleet SCD 10W** | | |

*Check every 8 hours, change every 250 hours*

## HYDRAULIC SYSTEM
Capacity: 130 liter (Change capacity)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Perlus H 46** | **Perlus H 32** | |

*Check every 8 hours, change every 2000 hours*

## GREASE POINTS/NIPPLES FRONT JOINT PINS

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Change every 100 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# HITACHI TRACKED EXCAVATORS EX EX 120 (1994-1994)

## GREASE POINTS/NIPPLES OTHERS

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Change every 100 hours*

## GREASE POINTS/NIPPLES SWING BEARING

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Change every 500 hours*

## GREASE POINTS/NIPPLES SWING INTERNAL GEAR

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Change every 500 hours*

## COOLING SYSTEM
Capacity: 16,4 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Coolant -38 Organic NF** | **Coolant -26** | |

*Check every 8 hours, change every 500 hours*

## SWING REDUCTION UNIT
Capacity: 3,2 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-4 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 250 hours, change every 1000 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# HITACHI TRACKED EXCAVATORS EX EX 120 (1994-1994)

**TRAVEL REDUCTION UNIT**
Capacity: 3,5 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-4 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 250 hours, change every 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367