

# HITACHI TRACKED EXCAVATORS EX EX 550H



**ENGINE** Cummins NTA855-C400  
Capacity: 44 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 8 hours, change every 250 hours*

**HYDRAULIC SYSTEM**  
Capacity: 560 liter (Change capacity)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

*Check every 8 hours, change every 1500 hours*

## GREASE POINTS/NIPPLES FRONT JOINT PINS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 50 hours*

## GREASE POINTS/NIPPLES OFF-SET FRONT JOINTS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 50 hours*

## GREASE POINTS/NIPPLES OTHERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 50 hours*

# HITACHI TRACKED EXCAVATORS EX EX 550H



## GREASE POINTS/NIPPLES SWING BEARING

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Labora Grease</b>	PRODUCT RECOMMENDATION 2 <b>Q5 MP Calcep Grease EP 2</b>	PRODUCT RECOMMENDATION 3 <b>MP Lithep Grease EP 2</b>

*Change every 500 hours*

## GREASE POINTS/NIPPLES SWING INTERNAL GEAR

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Labora Grease</b>	PRODUCT RECOMMENDATION 2 <b>Q5 MP Calcep Grease EP 2</b>	PRODUCT RECOMMENDATION 3 <b>MP Lithep Grease EP 2</b>

*Change every 500 hours*

## COOLING SYSTEM

Capacity: 71 liter

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Coolant -38 Organic NF</b>	PRODUCT RECOMMENDATION 2 <b>Coolant -26</b>	

*Check every 8 hours, change every 6 months*

## PUMP DRIVE UNIT

Capacity: 5 liter

USE Normal		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 <b>Agridiesel CRD+ 15W-40</b>	PRODUCT RECOMMENDATION 2 <b>Dieselfleet CD+ 15W-40</b>	PRODUCT RECOMMENDATION 3 <b>Multifleet SHPD 15W-40</b>

*Check every 250 hours, change every 1000 hours*

## SWING REDUCTION UNIT

Capacity: 13,2 liter

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Gearlube GL-4 80W-90</b>	PRODUCT RECOMMENDATION 2 <b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 250 hours, change every 1000 hours*

# HITACHI TRACKED EXCAVATORS EX EX 550H


**TRAVEL REDUCTION UNIT**

Capacity: 14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 250 hours, change every 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*