

# HITACHI TRACKED EXCAVATORS EX EX 8

(1994-1994)



**ENGINE** Isuzu  
Capacity: 1,9 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40***Check every 8 hours, change every 100 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Check every 8 hours, change every 100 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Check every 8 hours, change every 100 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Check every 8 hours, change every 100 hours*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40***Check every 8 hours, change every 50 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Check every 8 hours, change every 50 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Check every 8 hours, change every 50 hours*

# HITACHI TRACKED EXCAVATORS EX EX 8

## (1994-1994)



USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		
<i>Check every 8 hours, change every 50 hours</i>		

HYDRAULIC SYSTEM		
Capacity: 13 liter (Change capacity)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		
<i>Change every 1000 hours</i>		

COOLING SYSTEM		
Capacity: 2,3 liter		
USE		CLIMATE
Preferred, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	
<i>Check every 8 hours, change every 24 months/ 4000 hours</i>		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	
<i>Check every 8 hours, change every 6 months</i>		

FRONT JOINT PINS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

SWING BEARING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

# HITACHI TRACKED EXCAVATORS EX EX 8

## (1994-1994)



### SWING GEAR

#### USE

Normal

#### CLIMATE

Moderate

#### PRODUCT RECOMMENDATION 1

**Labora Grease**

#### PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

#### PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

### TRAVEL REDUCTION UNIT

Capacity: 0,33 liter

#### USE

Normal

#### CLIMATE

Moderate

#### PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

#### PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 1000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.