

# HITACHI TRACKED EXCAVATORS ZX / ZAXIS ZAXIS / ZX 125US-3

**ENGINE**

Capacity: 15,8 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 2****Synfleet SHPD 10W-40****PRODUCT RECOMMENDATION 3****Dieselfleet CD+ 15W-40***Check every 8 hours, change every 500 hours***HYDRAULIC SYSTEM**

Capacity: 62 liter (Hydraulic tank), Capacity: 120 liter (Total)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Perlus H 46***Check every 8 hours, change every 1500 hours***GREASE POINTS/NIPPLES FRONT JOINT PINS****USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2***Check every 8 hours, change every 250 hours***GREASE POINTS/NIPPLES SWING BEARING****USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2***Change every 500 hours***GREASE POINTS/NIPPLES SWING INTERNAL GEAR****USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2***Change every 500 hours*

# HITACHI TRACKED EXCAVATORS ZX / ZAXIS ZAXIS / ZX 125US-3



## COOLING SYSTEM

Capacity: 19 liter

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

*Check every 8 hours, change every 24 months/ 4000 hours*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 8 hours, change every 6 months*

## SWING REDUCTION UNIT

Capacity: 3,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 250 hours, change every 1000 hours*

## TRAVEL REDUCTION UNIT

Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 250 hours, change every 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*