

HITACHI TRACKED EXCAVATORS ZX / ZAXIS ZAXIS / ZX 130LCN-3 (2008 AND AFTER)



ENGINE Isuzu AJ-4JJ1X
Capacity: 17 liter

USE

Normal, fuel sulfur level > 2000 ppm

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40*Check every 8 hours, change every 250 hours***USE**

Normal, fuel sulfur level < 2000 ppm

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40*Check every 8 hours, change every 500 hours***HYDRAULIC SYSTEM**

Capacity: 70 liter (Hydraulic tank), Capacity: 170 liter (System)

USE

Preferred, extended

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46*Check every 8 hours, change every 5000 hours***GREASE POINTS/NIPPLES****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2**COOLING SYSTEM**

Capacity: 16 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

HITACHI TRACKED EXCAVATORS ZX / ZAXIS ZAXIS / ZX 130LCN-3 (2008 AND AFTER)



SWING REDUCTION UNIT

Capacity: 3,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours

TRAVEL REDUCTION UNIT

Capacity: 4 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.