HITACHI WHEELED LOADERS LX/ZW ZW250-5B ISUZU AH-6HK1X (2013 AND



AFTER)

ENGINE Isuzu AH-6HK1X Capacity: 31,6 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrisynth LSP Ultra FE 5W-30	Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30	

Check every 8 hours, change every 500 hours

DIFFERENTIAL FRONT

Capacity: 40 liter (+ hub reductions)

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR

Capacity: 40 liter (+ hub reductions)

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS FRONT

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS REAR

We are unable to give a standard recommendation for this component. Please contact our service department.

₹	
USE	
	Moderate
ours	
	CLIMATE
	Moderate
Lire	
h	hours

PRODUCT RECOMMENDATION

HITACHI WHEELED LOADERS LX/ZW ZW250-5B ISUZU AH-6HK1X (2013 AND



AFTER)

HYDRAULIC SYSTEM Capacity: 190 liter (Change capacity)	
USE	CLIMATE
Preferred	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Check every 8 hours, change every 4000 hours	

GREASE POINTS/NIPPLES				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

COOLING SYSTEM Capacity: 35 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.