

# HYDREMA BACKHOE LOADERS 604

## PERKINS 1004-40HR (1994-1998)



**ENGINE** Perkins 1004-40HR  
Capacity: 5,5 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40**

*Check every 10 hours, change every 400 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SCD 30**

*Check every 10 hours, change every 400 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 10W-40**

*Check every 10 hours, change every 400 hours*

### DIFFERENTIAL FRONT

Capacity: 8,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3

**Agrifluid HT**

*Check every 200 hours, change every 1000 hours/ 12 months*

### DIFFERENTIAL REAR

Capacity: 8,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3

**Agrifluid HT**

*Check every 200 hours, change every 1000 hours/ 12 months*

# HYDREMA BACKHOE LOADERS 604

## PERKINS 1004-40HR (1994-1998)



### HUB REDUCTIONS FRONT

Capacity: 0,6 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

## PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

## PRODUCT RECOMMENDATION 3

**Agrifluid HT***Check every 200 hours, change every 1000 hours/ 12 months*

### HUB REDUCTIONS REAR

Capacity: 0,6 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

## PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

## PRODUCT RECOMMENDATION 3

**Agrifluid HT***Check every 200 hours, change every 1000 hours/ 12 months*

### TRANSMISSION Powershift

Capacity: 17 liter, Capacity: 12 liter (Change capacity)

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20***Check every 10 hours, change every 1000 hours/ 12 months*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

## PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

## PRODUCT RECOMMENDATION 3

**Dieselfleet CD+ 15W-40***Check every 10 hours, change every 1000 hours/ 12 months*

## USE

Normal

## CLIMATE

Arctic

## PRODUCT RECOMMENDATION 1

**ATF Dexron II-D***Check every 10 hours, change every 1000 hours/ 12 months*

# HYDREMA BACKHOE LOADERS 604

## PERKINS 1004-40HR (1994-1998)



### HYDRAULIC SYSTEM

Capacity: 80 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

Check every 40 hours, change every 24 months/ 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

Check every 40 hours, change every 24 months/ 2000 hours

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

### COOLING SYSTEM

Capacity: 14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.