

HYDREMA BACKHOE LOADERS 806T (TILL 1990)

**ENGINE**

Capacity: 9 liter

| USE | | CLIMATE |
|-------------------------------|-------------------------------|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |

Check every 10 hours, change every 200 hours

| USE | | CLIMATE |
|-----------------------------|-----------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 |

*Check every 10 hours, change every 200 hours***DIFFERENTIAL FRONT**

Capacity: 13,5 liter

| USE | | CLIMATE |
|----------------------------------|-----------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Kroontrak MTH 10W-30 | Agrifluid HT |

*Check every 200 hours, change every 24 months/ 2400 hours***DIFFERENTIAL REAR**

Capacity: 13,5 liter

| USE | | CLIMATE |
|----------------------------------|-----------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Kroontrak MTH 10W-30 | Agrifluid HT |

*Check every 200 hours, change every 24 months/ 2400 hours***HUB REDUCTIONS FRONT**

Capacity: 4 liter

| USE | | CLIMATE |
|----------------------------------|-----------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Kroontrak MTH 10W-30 | Agrifluid HT |

Check every 200 hours, change every 24 months/ 2400 hours

HYDREMA BACKHOE LOADERS 806T (TILL 1990)



HUB REDUCTIONS REAR

Capacity: 4 liter

| USE | | CLIMATE |
|----------------------------------|-----------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Kroontrak MTH 10W-30 | Agrifluid HT |

Check every 200 hours, change every 24 months/ 2400 hours

TRANSMISSION Powershift

Capacity: 17 liter, Capacity: 10 liter (Change capacity)

| USE | | CLIMATE |
|------------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 20W-20 | | |

Check every 10 hours, change every 1200 hours/ 12 months

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |

Check every 10 hours, change every 1200 hours/ 12 months

| USE | | CLIMATE |
|--------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |

Check every 10 hours, change every 1200 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 125 liter

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 46 | | |

Check every 40 hours, change every 24 months/ 2400 hours

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 32 | | |

Check every 40 hours, change every 24 months/ 2400 hours

HYDREMA BACKHOE LOADERS 806T (TILL 1990)



GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

COOLING SYSTEM

Capacity: 23 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Check every 10 hours, change every 2400 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.