

HYDREMA BACKHOE LOADERS 906

PERKINS 1004-40THR (1994-1998)



ENGINE Perkins 1004-40THR
Capacity: 9 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Check every 10 hours, change every 400 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SCD 30

Check every 10 hours, change every 400 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SHPD 10W-40

Check every 10 hours, change every 400 hours

DIFFERENTIAL FRONT

Capacity: 16,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3

Agrifluid HT

Check every 200 hours, change every 1000 hours/ 12 months

DIFFERENTIAL REAR

Capacity: 16,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3

Agrifluid HT

Check every 10 hours, change every 1000 hours/ 12 months

HYDREMA BACKHOE LOADERS 906

PERKINS 1004-40THR (1994-1998)



HUB REDUCTIONS FRONT

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT

Check every 10 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS REAR

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT

Check every 10 hours, change every 1000 hours/ 12 months

TRANSFERBOX

Capacity: 6 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Check every 10 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W	ATF Dexron II-D	

Check every 10 hours, change every 1000 hours/ 12 months

HYDREMA BACKHOE LOADERS 906

PERKINS 1004-40THR (1994-1998)

**TRANSMISSION ZF WG 100**

Capacity: 17 liter, Capacity: 12 liter (Change capacity)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SCD 20W-20

Check every 10 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40

Check every 10 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1
ATF Dexron II-D

Check every 10 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 125 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1
Perlus H 46

Check every 40 hours, change every 24 months/ 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Perlus H 32

Check every 40 hours, change every 24 months/ 2000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
MoS2 Grease EP 2

HYDREMA BACKHOE LOADERS 906

PERKINS 1004-40THR (1994-1998)

**COOLING SYSTEM**

Capacity: 26 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26**

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.