

HYSTER FORKLIFT TRUCKS, PETROL/LPG H50FT (L177) MAZDA F2 (2006-2015)



ENGINE Mazda F2
Capacity: 4,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 10W-30

Check every 8 hours, change every 6 months/ 250 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 5W-30

Check every 8 hours, change every 6 months/ 250 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 10W-30

Change every 100 hours

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 5W-30

Change every 100 hours

DRIVE AXLE DRY BRAKE VERSION
Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 3

Gearlube GL-5 85W-140

Check every 6 months/ 500 hours, change every 12 months/ 2000 hours

TRANSMISSION DRY BRAKE VERSION

Capacity: 13 liter (aluminium case), Capacity: 20 liter (iron case)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30

Check every 6 months/ 500 hours, change every 12 months/ 2000 hours

HYSTER FORKLIFT TRUCKS, PETROL/LPG H50FT (L177) MAZDA F2 (2006-2015)



TRANSMISSION WET BRAKE VERSION

Capacity: 13 liter (aluminium case), Capacity: 20 liter (iron case)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 6 months/ 500 hours, change every 12 months/ 2000 hours

WET BRAKE AXLE CENTER SECTION

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 6 months/ 500 hours, change every 12 months/ 2000 hours

WET BRAKE AXLE PLANETARY HOUSING

Capacity: 0,5 liter (Left), Capacity: 2 liter (Right)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140

Check every 6 months/ 500 hours, change every 12 months/ 2000 hours

HYDRAULIC SYSTEM

Capacity: 39,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

Check every 6 months/ 500 hours, change every 24 months/ 4000 hours

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

Check every 6 months/ 500 hours, change every 24 months/ 2000 hours

HYSTER FORKLIFT TRUCKS, PETROL/LPG H50FT (L177) MAZDA F2 (2006-2015)



HYDRAULIC BRAKE SYSTEM DRY BRAKES

Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 6 months/ 500 hours, change every 12 months/ 2000 hours

HYDRAULIC BRAKE SYSTEM WET BRAKES

Capacity: 0,35 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 6 months/ 500 hours, change every 12 months/ 2000 hours

GREASE POINTS/NIPPLES BRAKE MASTER CYLINDER ROD END PIN

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 10W-30		

Check every 6 months/ 500 hours

GREASE POINTS/NIPPLES LIFT CHAIN

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

GREASE POINTS/NIPPLES MANUAL HYDRAULIC HAND LEVELERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 10W-30		

Check every 6 months/ 500 hours

HYSTER FORKLIFT TRUCKS, PETROL/LPG H50FT (L177) MAZDA F2 (2006-2015)



GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 6 months/ 500 hours

COOLING SYSTEM

Capacity: 10,6-11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 8 hours, change every 24 months/ 4000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.