

# HYUNDAI FORKLIFT TRUCKS, ELECTRIC B/BC/BCS/BH/BHA/BR/BRJ/BT/BTR/HBF/HBR 16BRJ-7



## HYDRAULIC SYSTEM

Capacity: 28 liter (Hydraulic tank (TF 700~TF 800)), Capacity: 32 liter (Hydraulic tank (TF 850)), Capacity: 25 liter (Hydraulic tank (~TF 670))

USE	CLIMATE
Normal	Mediterranean

### PRODUCT RECOMMENDATION 1

**Perlus H 68**

*Check every 10 hours, change every 2000 hours*

USE	CLIMATE
Normal	Moderate

### PRODUCT RECOMMENDATION 1

**Perlus H 46**

### PRODUCT RECOMMENDATION 2

**Perlus H 32**

*Check every 10 hours, change every 2000 hours*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Mediterranean

### PRODUCT RECOMMENDATION 1

**Labora Grease**

### PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

### PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

USE	CLIMATE
Normal	Moderate

### PRODUCT RECOMMENDATION 1

**Gear Grease EP 1**

## DRIVE UNIT

Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

### PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

### PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*