HYUNDAI FORKLIFT TRUCKS, LPG 15LC-7 HYUNDAI BETA L4GC (2008-2011)



| ENGINE Hyundai Beta L4GC Capacity: 3,9 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Asyntho 5W-30 | |

| DIFFERENTIAL FRONT Capacity: 3,5 liter | | | | | | |
|---|--------------------------|--------------------------|--|--|--|--|
| USE | | CLIMATE | | | | |
| Normal | | Moderate | | | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | | | |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Agrifluid HT | | | | |
| Check every 1 months/ 250 hours, change every 3 months/ 500 hours | | | | | | |
| USE | | CLIMATE | | | | |
| Initial service | | Moderate | | | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | | | |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Agrifluid HT | | | | |

Change every 50 hours

| TRANSMISSION POWERSHIFT 1/1 Capacity: 8,5 liter (+ torque converter) | | | | |
|---|--------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| SP Matic 2032 | | | | |
| Check every 50 hours, change every 6 months/ 1000 hours | | | | |

| use Initial service | | climate Moderate |
|--------------------------|--------------------------|---------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Matic 2032 | ATF Almirol | |

Change every 100 hours

HYUNDAI FORKLIFT TRUCKS, LPG 15LC-7 HYUNDAI BETA L4GC (2008-2011)



| HYDRAULIC SYSTEM Capacity: 30 liter (Optional), Capacity: 24,5 liter (Standard) | | | | |
|--|--------------------------|---------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Mediterranean | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| Perlus H 68 | | | | |
| Check every 10 hours, change every 2000 hours | | | | |
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Perlus H 46 | Perlus H 32 | | | |

Check every 10 hours, change every 2000 hours

| HYDRAULIC BRAKE SYSTEM Capacity: 0,5 liter | | | | |
|---|--|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| Drauliquid DOT 3 | | | | |
| Check every 10 hours, change every 6 months/ 1000 hours | | | | |

| | ~ | <i>,</i> | 0 | - | | |
|--|---|----------|---|---|--|--|
| | | | | | | |
| | | | | | | |
| | | | | | | |

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| USE | | CLIMATE |
| | | |
| Normal | | Moderate |
| | | |

| COOLING SYSTEM Capacity: 17 liter | | | |
|--------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant -38 Organic NF | Coolant -26 | | |
| Check every 50 hours, change every | 2000 hours | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

HYUNDAI FORKLIFT TRUCKS, LPG 15LC-7 HYUNDAI BETA L4GC (2008-2011)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.