

# HYUNDAI GRAVEMASKINE MED LARVEBÅND (INDIEN) R80 -> R215LC-7 CUMMINS 6BTAA5.9 (CUMMINS-INDIA)



**MOTOR** Cummins 6BTAA-5.9  
Kapacitet: 15 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 2  
**Synfleet SHPD 10W-40**

PRODUKTANBEFALING 3  
**Dieselfleet CD+ 15W-40**

## HYDRAULISK SYSTEM

Kapacitet: 180 liter (Hydrauliktank), Kapacitet: 290 liter (System)

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1  
**Perlus H 68**

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Perlus H 46**

PRODUKTANBEFALING 2  
**Perlus H 32**

## SMØREPUNKTER/NIPLER

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1  
**Labora Grease**

PRODUKTANBEFALING 2  
**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3  
**MP Lithep Grease EP 2**

ANVEND  
Normal

KLIMA  
Koldt

PRODUKTANBEFALING 1  
**Gear Grease EP 1**

## KØLESYSTEM

Kapacitet: 35 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Coolant -38 Organic NF**

PRODUKTANBEFALING 2  
**Coolant -26**

# HYUNDAI GRAVEMASKINE MED LARVEBÅND (INDIEN) R80 -> R215LC-7 CUMMINS 6BTAA5.9 (CUMMINS-INDIA)



## SPORDREV GEARKASSER

Kapacitet: 5,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube Racing 75W-140**

PRODUKTANBEFALING 2

**Unigear LS GL-3/GL-5 85W-140**

## SVINGREDUKTIONSGEARKASSE

Kapacitet: 5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube Racing 75W-140**

PRODUKTANBEFALING 2

**Unigear LS GL-3/GL-5 85W-140**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*