

HYUNDAI WHEELED EXCAVATORS R130W - > R170W-9S MITSUBISHI S6S-DT (2012 AND AFTER)



ENGINE Mitsubishi S6S-DT
Capacity: 16,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 2

Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 3

Dieselfleet LSP Ultra 10W-30

Check every 10 hours, change every 500 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 2

Armado Synth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 3

Armado Synth MSP 5W-40

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT

Capacity: 10,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 250 hours, change every 1000 hours

DIFFERENTIAL REAR

Capacity: 15,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 250 hours, change every 1000 hours

HUB REDUCTIONS FRONT

Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 250 hours, change every 1000 hours

HYUNDAI WHEELED EXCAVATORS R130W - > R170W-9S MITSUBISHI S6S-DT (2012 AND AFTER)



HUB REDUCTIONS REAR

Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 250 hours, change every 1000 hours

TRANSMISSION

Capacity: 3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Dieselfleet CD+ 15W-40

Check every 50 hours, change every 1000 hours

HYDRAULIC SYSTEM

Capacity: 160 liter (Hydraulic tank), Capacity: 270 liter (System)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus H 68

Check every 10 hours, change every 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus H 32

Check every 10 hours, change every 2000 hours

HYUNDAI WHEELED EXCAVATORS R130W - > R170W-9S MITSUBISHI S6S-DT (2012 AND AFTER)



GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

Change every 50 hours

COOLING SYSTEM

Capacity: 17,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours

SWING GEAR

Capacity: 1,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 50 hours, change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

Check every 50 hours, change every 1000 hours

HYUNDAI WHEELED EXCAVATORS R130W - > R170W-9S MITSUBISHI S6S-DT (2012 AND AFTER)


SWING REDUCTION GEARBOX

Capacity: 5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 50 hours, change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.