

HYUNDAI TRACKED EXCAVATORS (BRASIL) R140LC -> R260LC-9S CUMMINS QSB6.7



ENGINE Cummins QSB6.7
Capacity: 24 liter

USE	CLIMATE
Alternative, fuel sulfur level < 0,0015 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30

Check every 10 hours, change every 250 hours

USE	CLIMATE
Alternative, fuel sulfur level < 0,0015 %	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Check every 10 hours, change every 250 hours

HYDRAULIC SYSTEM

Capacity: 165 liter (Hydraulic tank), Capacity: 285 liter (System)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 10 hours, change every 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	

Check every 10 hours, change every 2000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

Change every 50 hours

HYUNDAI TRACKED EXCAVATORS (BRASIL) R140LC -> R260LC-9S CUMMINS QSB6.7

**COOLING SYSTEM**

Capacity: 35 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours

SWING GEAR

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

SWING REDUCTION GEARBOX

Capacity: 6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 50 hours, change every 1000 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 50 hours, change every 1000 hours

HYUNDAI TRACKED EXCAVATORS (BRASIL) R140LC -> R260LC-9S CUMMINS QSB6.7



TRACK DRIVE GEARBOXES

Capacity: 3,3 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 1000 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.