PRODUCT RECOMMENDATION

HYUNDAI TRACKED EXCAVATORS HX HX260L CUMMINS QSB6.7 (EU STAGE IV/TIER 4F) (2015 AND AFTER)

ENGINE Cummins QSB6.7
Capacity: 23,1 liter

USE	CLIMATE
Alternative, fuel sulfur level < 0,0015 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	**Agrisynth LSP Ultra 10W-40**	**Agrisynth MSP 10W-40**

FINAL DRIVE TRANSMISSIONS
Capacity: 6 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 85W-140	**Unigear LS GL-3/GL-5 85W-140**

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	**Syngear TDL 75W-90**

HYDRAULIC SYSTEM
Capacity: 275 liter (Hydraulic system including tank), Capacity: 160 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1
Perlus H 68

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Perlus H 46

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1
Perlus H 15

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

HYUNDAI TRACKED EXCAVATORS HX HX260L CUMMINS QSB6.7 (EU STAGE IV/TIER 4F) (2015 AND AFTER)

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

COOLING SYSTEM
Capacity: 40 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR)
Capacity: 27 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

SWING REDUCTION GEARBOX
Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	**Unigear LS GL-3/GL-5 85W-140**	

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	**Syngear TDL 75W-90**	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367