

HYUNDAI TRACKED EXCAVATORS R110 -> R290LC (1997-1998)

**ENGINE** Cummins 6CT8.3

| USE | | CLIMATE |
|-------------------------------|-------------------------------|-------------------------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Change every 250 hours/ 1 months

| USE | | CLIMATE |
|-----------------------------|-------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 | |

Change every 250 hours/ 1 months

| USE | | CLIMATE |
|-------------------------------|-------------------------------|-------------------------------|
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Change every 50 hours

| USE | | CLIMATE |
|-----------------------------|-------------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 | |

Change every 50 hours

HYDRAULIC SYSTEM

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 68 | | |

Change every 2000 hours/ 12 months

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus H 46 | Perlus H 32 | |

Change every 2000 hours/ 12 months

HYUNDAI TRACKED EXCAVATORS R110 -> R290LC (1997-1998)



GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

SWING REDUCTION GEARBOX

| USE | | CLIMATE |
|--------------------------------|-------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube Racing 75W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Change every 1000 hours/ 6 months

TRACK DRIVE GEARBOXES

| USE | | CLIMATE |
|------------------------------|-------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Change every 1000 hours/ 6 months

TRACK IDLERS

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |

TRACK PINS

| USE | | CLIMATE |
|------------------------------|-------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

TRACK ROLLERS

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

PRODUCT RECOMMENDATION

HYUNDAI TRACKED EXCAVATORS R110 -> R290LC (1997-1998)



Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.