

# HYUNDAI WHEELED LOADERS HL

## HL740TM-3 CUMMINS 6BT5.9 (1999-2004)



**ENGINE** Cummins 6BT5.9  
Capacity: 16,4 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2  
**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3  
**Dieselfleet CD+ 15W-40**

*Change every 250 hours/ 1 months*

USE  
Initial service

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2  
**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3  
**Dieselfleet CD+ 15W-40**

*Change every 50 hours*

**DIFFERENTIAL FRONT LIMITED SLIP**  
Capacity: 40 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Gearlube LS 80W-90**

*Change every 1000 hours/ 6 months*

**DIFFERENTIAL REAR LIMITED SLIP**  
Capacity: 40 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Gearlube LS 80W-90**

*Change every 1000 hours/ 6 months*

**TRANSMISSION POWERSHIFT 4/3**  
Capacity: 25 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**ATF Dexron II-D**

*Change every 1000 hours/ 6 months*

# HYUNDAI WHEELED LOADERS HL

## HL740TM-3 CUMMINS 6BT5.9 (1999-2004)



### HYDRAULIC SYSTEM

Capacity: 75 liter (Hydraulic tank), Capacity: 120 liter (System)

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Normal                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>Perlus H 68</b>       |  |               |

Change every 2000 hours/ 12 months

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 46</b>       | <b>Perlus H 32</b>       |          |

Change every 2000 hours/ 12 months

### GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Mediterranean                |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Gear Grease EP 1</b>  |  |          |

### COOLING SYSTEM

Capacity: 35 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.