HYUNDAI WHEELED LOADERS HL HL770-9 (2010-2012)



| ENGINE Cummins QSL9 Capacity: 23 liter | | |
|---|-------------------------------|------------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth MSP 10W-40 | Agridiesel MSP 15W-40 | Dieselfleet LSP Ultra 10W-30 |
| Check every 10 hours, change every 500 | hours | _ |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP Ultra 10W-40 | Armado Synth LSP Ultra 10W-40 | Armado Synth MSP 5W-40 |

| DIFFERENTIAL FRONT ZF Capacity: 51 liter (+ hub reductions) | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Agrifluid HT |

Change every 1500 hours

Check every 10 hours, change every 500 hours

| DIFFERENTIAL REAR ZF Capacity: 43 liter (+ hub reductions) | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Agrifluid HT |
| Change every 1500 hours | • | |

| HUB REDUCTIONS FRONT ZF | | | |
|---------------------------|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Agrifluid HT | |
| Change every 1500 hours | | 1 | |

HYUNDAI WHEELED LOADERS HL HL770-9 (2010-2012)



| HUB REDUCTIONS REAR ZF | | | |
|---------------------------|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Agrifluid HT | |
| Change every 1500 hours | | | |

Change every 1500 hours

| TRANSMISSION Powershift Capacity: 43 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |
| Charles avant 40 basses about a second | 10001 | |

Check every 10 hours, change every 1000 hours

| HYDRAULIC SYSTEM Capacity: 200 liter (Hydraulic tank), Capacity: 320 liter (System) | | |
|---|--------------------------------------|-------------------------|
| use Normal | | сымате Mediterranean |
| PRODUCT RECOMMENDATION 1 Perlus H 68 | | |
| Check every 10 hours, change every 2000 hours | | |
| use Normal | | climate Moderate |
| PRODUCT RECOMMENDATION 1 Perlus H 46 | PRODUCT RECOMMENDATION 2 Perlus H 32 | |
| Check every 10 hours, change every 2000 hours | | |

USE CLIMATE
Normal Mediterranean

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3

Labora Grease Q5 MP Calcep Grease EP 2 MP Lithep Grease EP 2

Change every 50 hours

| USE | CLIMATE |
|--------------------------|----------|
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gear Grease EP 1 | |
| Change every 50 hours | · |

KROON-OIL B.V. Postbus 149 7600 AC Almelo

HYUNDAI WHEELED LOADERS HL HL770-9 (2010-2012)



| COOLING SYSTEM Capacity: 56 liter | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |
| Check over 40 hours share even 2000 hours | | |

Check every 10 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.