

HYUNDAI WHEELED LOADERS (BRASIL)

HL HL740-9B CUMMINS 6BTA5.9 (2012 AND AFTER)



ENGINE Cummins 6BTA5.9
Capacity: 15 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 3
Dieselfleet LSP Ultra 10W-30

Check every 10 hours, change every 500 hours

USE
Normal

CLIMATE
Cold

PRODUCT RECOMMENDATION 1
Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 2
Armado Synth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 3
Armado Synth MSP 5W-40

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT

Capacity: 21,2 liter (+ hub reductions)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube LS 80W-90

Change every 1000 hours

DIFFERENTIAL REAR

Capacity: 21,2 liter (+ hub reductions)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube LS 80W-90

Change every 1000 hours

TRANSMISSION POWERSHIFT ZF 4WG160 4/3

Capacity: 25 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40

Change every 1000 hours

HYUNDAI WHEELED LOADERS (BRASIL)

HL HL740-9B CUMMINS 6BTA5.9 (2012 AND AFTER)

**HYDRAULIC SYSTEM**

Capacity: 151 liter (Hydraulic tank), Capacity: 184 liter (System)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 10 hours, change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	

*Check every 10 hours, change every 2000 hours***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

*Change every 50 hours***COOLING SYSTEM**

Capacity: 34 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.