

HYUNDAI WHEELED LOADERS (INDIA) SL SL733S YUCHAI YC6J125Z-T20 (TIER 2)



ENGINE Yuchai YC6J125Z-T20
Capacity: 16 liter

USE	CLIMATE
Normal, fuel sulfur level <0,5 %	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 250 hours*

USE	CLIMATE
Normal, fuel sulfur level <0,5 %	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40*Change every 250 hours*

USE	CLIMATE
Normal, fuel sulfur level <0,5 %	Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 250 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 100 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40*Change every 100 hours*

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 100 hours*

HYUNDAI WHEELED LOADERS (INDIA) SL SL733S YUCHAI YC6J125Z-T20 (TIER 2)

**DIFFERENTIAL FRONT**

Capacity: 18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours

DIFFERENTIAL REAR

Capacity: 18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours

TRANSMISSION POWERSHIFT YJ315LH/BD08XD 4/2

Capacity: 43 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

HYDRAULIC SYSTEM

Capacity: 160 liter (System), Capacity: 90 liter (Tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 15		

HYUNDAI WHEELED LOADERS (INDIA) SL SL733S YUCHAI YC6J125Z-T20 (TIER 2)

**BRAKE (AIR BOOSTER)**

Capacity: 1 liter (Front), Capacity: 1 liter (Rear)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

COOLING SYSTEM

Capacity: 34 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.