HYUNDAI ROAD ROLLERS HR HR110C-9 DEUTZ TCD 2012 L04 (2010 AND AFTER)



ENGINE Deutz TCD 2012 L04 2V Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Change every 500 hours/ 12 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Change avery EQ hours	1	

Change every 50 hours

DIFFERENTIAL REAR Dana Spicer 602/112/105-100			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			
Check every 500 hours, change every	1500 hours	·	

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 500 hours	

mange every 500 hours

HYDRAULIC SYSTEM Capacity: 106 liter (Hydraulic tank)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 500 hours/ 12 months	· · · ·
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change aver EO have	

Change every 50 hours

HYUNDAI ROAD ROLLERS HR HR110C-9 DEUTZ TCD 2012 L04 (2010 AND AFTER)



COOLING SYSTEM Capacity: 15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

DRUM DRIVE GEARBOX		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 500 hours, change every 150	0 hours	
USE		CLIMATE

002	
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 500 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.