

INGERSOLL RAND COMPACTORS, SD SERIES SD-105TF



ENGINE Cummins B3.9
Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	

Change every 6 months/ 500 hours

DIFFERENTIALS
Capacity: 7,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 1000 hours/ 12 months

PLANETARY GEARS
Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 1000 hours/ 12 months

TORQUE HUB DRUM DRIVE
Capacity: 3,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1000 hours/ 12 months

HYDROSTATIC DRIVE
Capacity: 84 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 1000 hours/ 12 months

INGERSOLL RAND COMPACTORS, SD SERIES SD-105TF



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 16,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 1000 hours/ 12 months

DRUM CARRIER

Capacity: 0,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		

Change every 1000 hours/ 12 months

DRUM ECCENTRIC

Capacity: 7,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		

Change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.