

JCB TRACKED EXCAVATORS 8010 CTS STAGE IIIA/T3 (M1149553 ->) (2004-2010)



ENGINE Perkins 403D-11
Capacity: 4,9 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 15W-40

Check every 10 hours, change every 3 months/ 500 hours

HYDRAULIC SYSTEM

Capacity: 16 liter (Hydraulic tank), Capacity: 21 liter (System)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Perlus H 46

PRODUCT RECOMMENDATION 2
Perlus AF 46

Check every 10 hours, change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES OTHERS

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Labora Grease

PRODUCT RECOMMENDATION 2
Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3
MP Lithep Grease EP 2

Check every 10 hours

COOLING SYSTEM

Capacity: 4,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Coolant SP 15+

PRODUCT RECOMMENDATION 2
Coolant SP 12

PRODUCT RECOMMENDATION 3
Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

SWING RING BEARINGS

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Labora Grease

PRODUCT RECOMMENDATION 2
Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3
MP Lithep Grease EP 2

Check every 50 hours

JCB TRACKED EXCAVATORS 8010 CTS STAGE IIIA/T3 (M1149553 ->) (2004-2010)



SWING RING GEAR TEETH

We are unable to give a standard recommendation for this component. Please contact our service department.

TRAVEL REDUCTION UNIT

Capacity: 0,3 liter (each)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Check every 1 months/ 250 hours, change every 3 months/ 500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.