

JCB WHEELED LOADERS 436 HT (1994-1999)


ENGINE Cummins 6CT8.3-170

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 250 hours

ENGINE Perkins 1006.6T

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 250 hours

DIFFERENTIAL FRONT

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 500 hours

DIFFERENTIAL REAR

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 500 hours

HUB REDUCTIONS FRONT

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 500 hours

JCB WHEELED LOADERS 436 HT (1994-1999)



HUB REDUCTIONS REAR

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Change every 500 hours</i>		

TRANSMISSION ZF

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
<i>Change every 1000 hours</i>		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT
<i>Change every 1000 hours</i>		

HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 32		
<i>Change every 2000 hours</i>		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.