

JCB ARTICULATED DUMP TRUCKS 722

CUMMINS QSB6.7 (2010 AND AFTER)



ENGINE Cummins QSB6.7
Capacity: 14 liter

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Change every 100 hours

USE	CLIMATE
Fuel sulfur level <0,5%	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 500 hours/ 6 months

USE	CLIMATE
Fuel sulfur level 0,5-1 %	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 6 months/ 375 hours

USE	CLIMATE
Fuel sulfur level >1%	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 6 months/ 250 hours

DIFFERENTIAL FRONT ZF AP9
Capacity: 17 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

DIFFERENTIAL INTERMEDIATE ZF AP9
Capacity: 17 liter (Axle), Capacity: 1,5 liter (Differential)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

JCB ARTICULATED DUMP TRUCKS 722

CUMMINS QSB6.7 (2010 AND AFTER)

**DIFFERENTIAL REAR ZF AP9**

Capacity: 17 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours***HUB REDUCTIONS FRONT**

Capacity: 3 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours***HUB REDUCTIONS INTERMEDIATE**

Capacity: 3 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours***HUB REDUCTIONS REAR**

Capacity: 3 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours***TRANSMISSION ZF 6WG210 6/3**

Capacity: 27 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

PRODUCT RECOMMENDATION 3

ATF Dexron II-D*Check every 100 hours, change every 1000 hours/ 12 months*

JCB ARTICULATED DUMP TRUCKS 722

CUMMINS QSB6.7 (2010 AND AFTER)



HYDRAULIC SYSTEM

Capacity: 88 liter (Hydraulic tank), Capacity: 165 liter (System)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 32*Check every 10 hours, change every 2000 hours/ 24 months*

GREASE POINTS/NIPPLES

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease*Check every 100 hours*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 10 hours*

COOLING SYSTEM

Capacity: 27 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF*Check every 10 hours, change every 2000 hours/ 24 months*

PROPSHAFT CENTRE BEARING

Capacity: 3,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.