## JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 535-140 HIVIZ USA (93 KW) STAGE IIIB/T4I (2014 AND AFTER)



<b>ENGINE</b> JCB Ecomax T4i Capacity: 15 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Armado Synth MSP 5W-40	

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL FRONT Capacity: 17,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Charles and FO have a harrier average of the	ntha/E00 haven	

Check every 50 hours, change every 6 months/ 500 hours

CLIMATE
Moderate

Check every 50 hours, change every 6 months/ 500 hours

HUB REDUCTIONS FRONT Capacity: 1,9 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 50 hours, change every 6 months/ 500 hours		

HUB REDUCTIONS REAR Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 50 hours, change every 6 mo	500 hours	

## JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 535-140 HIVIZ USA (93 KW) STAGE IIIB/T4I (2014 AND AFTER)



TRANSMISSION POWERSHIFT PS760 Capacity: 21 liter (Change capacity), Capacity: 23 liter (Dry fill)		
USE	CLIMATE	
Normal	Mediterranean	
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 1000 hours/ 12 month	hs	
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 10 hours, change every 1000 hours/ 12 month	hs	
HYDRAULIC SYSTEM Capacity: 127 liter (Hydraulic tank)		
USE	CLIMATE	
Normal	Moderate	

Check every 50 hours, change every 2000 hours/24 months

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 15	
Check every 10 hours, change every 2000 hours/ 24 months	

PRODUCT RECOMMENDATION 2

Perlus H 46

USE CLIMATE
Normal Moderate

PRODUCT RECOMMENDATION 1
HT Q9 High Grade Grease

## JCB TELESCOPIC HANDLERS (USA) LOADALL/AGRI 535-140 HIVIZ USA (93 KW) STAGE IIIB/T4I (2014 AND AFTER)



COOLING SYSTEM Capacity: 28 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 10 hours, change eve	ery 2000 hours/ 24 months	1

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.