

JCB TELESCOPIC HANDLERS 530 AB, 767001->



ENGINE Perkins 1004-4T (AB)
Capacity: 10 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Multifleet SHPD 10W-40	

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

DIFFERENTIAL FRONT
Capacity: 18 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	
Agrifluid HT	

DIFFERENTIAL REAR
Capacity: 18 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	
Agrifluid HT	

HUB REDUCTIONS FRONT
Capacity: 2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	
Agrifluid HT	

JCB TELESCOPIC HANDLERS 530 AB, 767001->



HUB REDUCTIONS REAR

Capacity: 2 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

TRANSMISSION

Capacity: 21 liter, Capacity: 23 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF-F (Ford)		

HYDRAULIC SYSTEM

Capacity: 112 liter (Hydraulic tank)

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

HYDRAULIC BRAKE SYSTEM

Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

JCB TELESCOPIC HANDLERS 530 AB, 767001->

**COOLING SYSTEM**

Capacity: 23 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.