

## JCB TELESCOPIC HANDLERS 532 RJ



**ENGINE** Perkins 1104C-44TA (RJ)  
Capacity: 10 liter

| USE                          |                               | CLIMATE                       |
|------------------------------|-------------------------------|-------------------------------|
| Normal                       |                               | Mediterranean                 |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

**DIFFERENTIAL FRONT**  
Capacity: 18 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Agrifluid HT</b>      |  |          |

**DIFFERENTIAL REAR**  
Capacity: 18 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Agrifluid HT</b>      |  |          |

**HUB REDUCTIONS FRONT**  
Capacity: 2 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Agrifluid HT</b>      |  |          |

**HUB REDUCTIONS REAR**  
Capacity: 2 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Agrifluid HT</b>      |  |          |

**JCB TELESCOPIC HANDLERS 532 RJ****TRANSMISSION**

Capacity: 21 liter, Capacity: 23 liter (Dry fill)

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Gear Oil Alcat 10W</b> |  |          |

**HYDRAULIC SYSTEM**

Capacity: 131 liter (Hydraulic tank)

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Tropical |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 46</b>       | <b>Perlus AF 46</b>      |          |

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 32</b>       | <b>Perlus AF 32</b>      |          |

**HYDRAULIC BRAKE SYSTEM**

Capacity: 3 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Perlus H 15</b>       |  |          |

**GREASE POINTS/NIPPLES**

| USE                            |                          | CLIMATE                         |
|--------------------------------|--------------------------|---------------------------------|
| Normal                         |                          | Moderate                        |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3        |
| <b>HT Q9 High Grade Grease</b> | <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> |

**COOLING SYSTEM**

Capacity: 23 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

# JCB TELESCOPIC HANDLERS 532 RJ



*inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*