

JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 40IC YANMAR 3TNE68



ENGINE Yanmar 3TNE68
Capacity: 2,4 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

Change every 6 months/ 300 hours

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

PRODUCT RECOMMENDATION 2

HDX 30

Change every 6 months/ 300 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 10W-40

Change every 6 months/ 300 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

PRODUCT RECOMMENDATION 2

HDX 10W

Change every 6 months/ 300 hours

HYDRAULIC SYSTEM

Capacity: 64 liter (System), Capacity: 53 liter (Tank)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30

Change every 1200 hours/ 24 months

GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

Check every 3 months/ 150 hours

JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 40IC YANMAR 3TNE68



COOLING SYSTEM

Capacity: 1 liter (Engine only)

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

BOOM PINS/BUSHES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

SWING BEARING

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 3 months/ 150 hours

SWING BEARING GEAR TEETH

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 3 months/ 150 hours

SWING WORM GEAR BEARING

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 1200 hours/ 24 months

JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 40IC YANMAR 3TNE68



WHEEL BEARINGS

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 1200 hours/ 24 months

WHEEL TORQUE HUB

Capacity: 0,5 liter (each hub)

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 3 months/ 150 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.