

JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 60H DEUTZ F3L912

**ENGINE** Deutz F3L-912

Capacity: 9 liter, Filter capacity: 1 liter

| USE | | CLIMATE |
|-------------------------------|-------------------------------|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |

Check every 10 hours, change every 250 hours

| USE | | CLIMATE |
|-----------------------------|-----------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 |

*Check every 10 hours, change every 250 hours***HYDRAULIC SYSTEM**

Capacity: 265 liter (System), Capacity: 218 liter (Tank)

| USE | | CLIMATE |
|----------------------------------|--------------------------|-----------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

*Check every 10 hours, change every 2000 hours***GREASE POINTS/NIPPLES**

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

*Change every 100 hours***STEER SPINDLE**

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 100 hours

JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 60H DEUTZ F3L912



SWING BEARING

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 100 hours

SWING BEARING GEAR TEETH

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 100 hours

SWING DRIVE HUB

Capacity: 0,5 liter

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 50 hours, change every 2000 hours

WHEEL BEARINGS

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 500 hours

WHEEL TORQUE HUB

Capacity: 1,3 liter (each hub)

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 50 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.