

# JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 740AJ FORD LRG-425



**ENGINE** Ford LRG-425  
Capacity: 4,25 liter

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Kroontrak CVT 10W-40</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Kroontrak MTH 10W-30</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Multifleet SHPD 10W-40</b>
----------------------------------------------------------------	----------------------------------------------------------------	------------------------------------------------------------------

*Change every 3 months/ 150 hours*

**HUB REDUCTIONS FRONT**  
Capacity: 0,5 liter (each hub)

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Gearlube GL-5 80W-90</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Unigear HS GL-3/GL-5 80W-90</b>	
----------------------------------------------------------------	-----------------------------------------------------------------------	--

*Check every 3 months/ 150 hours, change every 24 months/ 1200 hours*

**HUB REDUCTIONS REAR**  
Capacity: 0,5 liter (each hub)

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Gearlube GL-5 80W-90</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Unigear HS GL-3/GL-5 80W-90</b>	
----------------------------------------------------------------	-----------------------------------------------------------------------	--

*Check every 3 months/ 150 hours, change every 24 months/ 1200 hours*

## HYDRAULIC SYSTEM

Capacity: 151,4 liter (Tank), Capacity: 291,4 liter (Total)

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Agrifluid Synth XHP Ultra</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Agrifluid HT-Plus</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Kroontrak MTH 10W-30</b>
---------------------------------------------------------------------	-------------------------------------------------------------	----------------------------------------------------------------

*Change every 1200 hours/ 24 months*

## GREASE POINTS/NIPPLES

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Labora Grease</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Q5 MP Calcep Grease EP 2</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>MP Lithep Grease EP 2</b>
---------------------------------------------------------	--------------------------------------------------------------------	-----------------------------------------------------------------

*Check every 3 months/ 150 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the*

PRODUCT RECOMMENDATION

# JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 740AJ FORD LRG- 425



*information contained herein is subject to changes without notification.*