## JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 800A CATERPILLAR 3044C, S/NO. 83332 ->



<b>ENGINE</b> Caterpillar 3044C/3,4 Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 3 months/ 150 hours

HUB REDUCTIONS FRONT Capacity: 1,3 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Charles avaired 2 magnified / 4EO house	phongs over 24 months/1200 hours	<u>'</u>

Check every 3 months/ 150 hours, change every 24 months/ 1200 hours

HUB REDUCTIONS REAR Capacity: 1,3 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 3 months/ 150 hours, of	change every 24 months/ 1200 hours	'

HYDRAULIC SYSTEM Capacity: 291 liter (Complete), Capacity: 151 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 8 hours, change every 24 months/ 1200 hours		

COOLING SYSTEM Capacity: 5,5 liter (Engine only)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

## JLG BOOM LIFTS WITH INTERNAL **COMBUSTION ENGINE 800A CATERPILLAR** 3044C, S/NO. 83332 ->



SWING BEARING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 3 months/ 150 hours		-

Change every 3 months/ 150 hours

WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 1200 hours/24 mon	ths	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.