

# JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 800AJ DEUTZ F4M-2011F, S/NO. -> 83332

**ENGINE** Deutz F4M-2011F

Capacity: 15 liter (Complete), Capacity: 10,5 liter (Engine only), Capacity: 4,5 liter (Oil cooler)

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

## PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40**

## PRODUCT RECOMMENDATION 3

**Multifleet SHPD 20W-50***Check every 8 hours, change every 12 months/ 1200 hours*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

## PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

## PRODUCT RECOMMENDATION 3

**Multifleet SHPD 10W-40***Check every 8 hours, change every 12 months/ 1200 hours***HUB REDUCTIONS FRONT**

Capacity: 0,5 liter (each hub)

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 3 months/ 150 hours, change every 24 months/ 1200 hours***HUB REDUCTIONS REAR**

Capacity: 0,5 liter (each hub)

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 3 months/ 150 hours, change every 24 months/ 1200 hours***HYDRAULIC SYSTEM**

Capacity: 291 liter (Complete), Capacity: 151 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

## PRODUCT RECOMMENDATION 2

**Agrifluid HT-Plus**

## PRODUCT RECOMMENDATION 3

**Kroontrak MTH 10W-30***Check every 8 hours, change every 24 months/ 1200 hours*

# JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 800AJ DEUTZ F4M-2011F, S/NO. -> 83332



## SWING BEARING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 3 months/ 150 hours*

## WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 1200 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*