

JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 80HX +(6) FORD LSG 423



ENGINE Ford LSG-423
Capacity: 4,7 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1
Kroontrak CVT 10W-40

Check every 10 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2
HDX 20W-50

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Check every 10 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1
Asyntho 5W-30

Check every 10 hours

HYDRAULIC SYSTEM

Capacity: 250 liter (System), Capacity: 208 liter (Tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30

Change every 1200 hours/ 24 months

SWING BEARING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Labora Grease

PRODUCT RECOMMENDATION 2
Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3
MP Lithep Grease EP 2

Change every 3 months/ 150 hours

JLG BOOM LIFTS WITH INTERNAL COMBUSTION ENGINE 80HX +(6) FORD LSG 423



SWING BEARING GEAR TEETH

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Labora Grease	PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2	PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2

Change every 600 hours/ 12 months

SWING REDUCTION UNIT

Capacity: 0,5 liter

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	

Change every 600 hours/ 12 months

WHEEL BEARINGS

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Labora Grease	PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2	PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2

Change every 600 hours/ 12 months

WHEEL DRIVE HUB

Capacity: 1,3 liter (each hub)

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	

Change every 1200 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.