

# JLG TELEHANDLERS 3507 PERKINS 1104C-44 (1160000358 ->)



**ENGINE** Perkins 1104C-44  
Capacity: 8,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 10 hours, change every 250 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 10 hours, change every 50 hours*

**DIFFERENTIAL FRONT**  
Capacity: 7,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Agrifluid HT-Plus</b>	

*Check every 250 hours, change every 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	
<b>Gearlube LS 80W-90</b>	

*Change every 50 hours*

**DIFFERENTIAL REAR**  
Capacity: 7,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Agrifluid HT-Plus</b>	

*Check every 250 hours, change every 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	
<b>Agrifluid HT-Plus</b>	

*Change every 50 hours*

# JLG TELEHANDLERS 3507 PERKINS 1104C-44 (1160000358 ->)



## TRANSFERBOX

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus***Check every 250 hours, change every 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus***Change every 50 hours*

## TRANSMISSION POWERSHIFT Dana

Capacity: 12,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus***Check every 250 hours, change every 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus***Change every 50 hours*

## HYDRAULIC SYSTEM

Capacity: 160 liter (Hydraulic tank), Capacity: 246 liter (System)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus***Check every 10 hours, change every 1500 hours*

# JLG TELEHANDLERS 3507 PERKINS 1104C-44 (1160000358 ->)



## COOLING SYSTEM

Capacity: 19,7 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

## PRODUCT RECOMMENDATION 2

**Coolant -26***Check every 10 hours, change every 1500 hours*

## WHEEL DRIVE HUB

Capacity: 1,4 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus***Check every 250 hours, change every 1000 hours*

## USE

Initial service

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus***Change every 50 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.