JLG TELEHANDLERS G9-43A CUMMINS QSB3.3 STAGE IIIA/T3 (0160040675 -0160048657)



ENGINE Cummins QSB3.3 Capacity: 7,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT Capacity: 8,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 250 hours, change every 100	0 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Change every 250 hours		

DIFFERENTIAL REAR Capacity: 12,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	
Check every 250 hours, change eve	1000 hours

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	
Change every 250 hours	

Change every 250 hours

JLG TELEHANDLERS G9-43A CUMMINS QSB3.3 STAGE IIIA/T3 (0160040675 - 0160048657)



,		
HUB REDUCTIONS FRONT Capacity: 1,65 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 250 hours, change every 100	00 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Change every 250 hours		
HUB REDUCTIONS REAR Capacity: 1,65 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 250 hours, change every 100	00 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Change every 250 hours		
TRANSFERBOX		
Capacity: 1,4 liter		Ol Blaze
use Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1		Moderate
Agrifluid HT-Plus		
Check every 250 hours, change every 100	l 10 hours	<u> </u>
USE	o nouro	CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Change every 250 hours	1	ı

JLG TELEHANDLERS G9-43A CUMMINS QSB3.3 STAGE IIIA/T3 (0160040675 - 0160048657)



TRANSMISSION POWERSHIFT 4/3 Capacity: 15,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 10 hours, change every 1000	hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Change every 250 hours		
	·	

HYDRAULIC SYSTEM Capacity: 88,2 liter (Reservoir), Cap	acity: 151 liter (System)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT-Plus			
Check every 10 hours, change ever	y 1500 hours	'	

COOLING SYSTEM Capacity: 17 liter (System)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

Check every 50 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.