JLG TELEHANDLERS G9-43A PERKINS 1104-C 44T (0160007868 - 0160040674)



ENGINE Perkins 1104C-44T Capacity: 6,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT Capacity: 8,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 250 hours, change every 1000 hours		

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	
Change every 250 hours	·

DIFFERENTIAL REAR Capacity: 12,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

Check every 250 hours, change every 1000 hours

use Initial service	climate Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	
Champe aver 250 hours	

Change every 250 hours

JLG TELEHANDLERS G9-43A PERKINS 1104-C 44T (0160007868 - 0160040674)



HUB REDUCTIONS FRONT Capacity: 1,65 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 250 hours, change every 1000 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Change every 250 hours		

HUB REDUCTIONS REAR Capacity: 1,65 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

Check every 250 hours, change every 1000 hours

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

Change every 250 hours

TRANSFERBOX Capacity: 1,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

Check every 250 hours, change every 1000 hours

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	
Change every 250 hours	·

JLG TELEHANDLERS G9-43A PERKINS 1104-C 44T (0160007868 - 0160040674)



TRANSMISSION POWERSHIFT 4/3 Capacity: 12,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 10 hours, change every 1000 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Change every 250 hours		

HYDRAULIC SYSTEM Capacity: 88,2 liter (Reservoir), Capacity: 151 liter (System)		
CLIMATE		
Moderate		

Check every 10 hours, change every 1500 hours

COOLING SYSTEM Capacity: 20,8 liter (System)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 50 hours, change every 1500 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.