

# JOHN DEERE (TIMBERJACK) FORWARDERS 1710B

**ENGINE**

Capacity: 29,9 liter

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 2****Dieselfleet CD+ 15W-40****PRODUCT RECOMMENDATION 3****Multifleet SHPD 15W-40***Change every 500 hours***USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Synfleet SHPD 10W-40****PRODUCT RECOMMENDATION 2****Multifleet SHPD 10W-40***Change every 500 hours***DIFFERENTIAL**

Capacity: 32 liter (Front), Capacity: 14 liter (Rear)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90****PRODUCT RECOMMENDATION 3****Gearlube GL-5 80W-90***Change every 2000 hours***HUB REDUCTIONS**

Capacity: 5 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90****PRODUCT RECOMMENDATION 3****Gearlube GL-5 80W-90***Change every 2000 hours***SWING REDUCTION UNIT LOADER**

Capacity: 7 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90****PRODUCT RECOMMENDATION 3****Gearlube GL-5 80W-90**

# JOHN DEERE (TIMBERJACK) FORWARDERS 1710B

**TRANSFERBOX HIGH/LOW**

Capacity: 4,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	<b>Gearlube GL-5 80W-90</b>

*Change every 1000 hours***BOGIE CASING**

Capacity: 65 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	<b>Gearlube GL-5 80W-90</b>

*Change every 2000 hours***HYDRAULIC SYSTEM**

Capacity: 175-190 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus H 68</b>	

*Change every 1000 hours*

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Change every 1000 hours***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>ATF Dexron II-D</b>	<b>ATF-F (Ford)</b>	

# JOHN DEERE (TIMBERJACK) FORWARDERS 1710B



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## COOLING SYSTEM

Capacity: 29 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	<b>Coolant -33 MPG</b>

*Change every 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*