

JOHN DEERE CONSTRUCTION TRACKED EXCAVATORS 75D TIER 3/STAGE IIIA (2008-2021)



ENGINE Isuzu 4LE2X
Capacity: 12,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Check every 10 hours, change every 250 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 56 liter (Hydraulic tank), Capacity: 100 liter (System)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 5000 hours

USE	CLIMATE
Fluid analysis	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 500 hours

COOLING SYSTEM

Capacity: 10,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

USE	CLIMATE
Fluid analysis	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 500 hours

TRAVEL REDUCTION UNIT

Capacity: 1,2 liter

JOHN DEERE CONSTRUCTION TRACKED EXCAVATORS 75D TIER 3/STAGE IIIA (2008- 2021)



USE Normal	CLIMATE Mediterranean
---------------	--------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 85W-140	PRODUCT RECOMMENDATION 2 Unigear LS GL-3/GL-5 85W-140	
--	---	--

Check every 250 hours, change every 2000 hours

USE Normal	CLIMATE Moderate
---------------	---------------------

PRODUCT RECOMMENDATION 1 SP Gear 1011	PRODUCT RECOMMENDATION 2 Syngear TDL 75W-90	PRODUCT RECOMMENDATION 3 Gearlube GL-5 80W-90
---	---	---

Check every 250 hours, change every 2000 hours

USE Normal	CLIMATE Cold
---------------	-----------------

PRODUCT RECOMMENDATION 1 SP Gear 1081	PRODUCT RECOMMENDATION 2 SP Gear 5015	
---	---	--

Check every 250 hours, change every 2000 hours

USE Fluid analysis	CLIMATE Mediterranean
-----------------------	--------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 85W-140	PRODUCT RECOMMENDATION 2 Unigear LS GL-3/GL-5 85W-140	
--	---	--

Check every 250 hours

USE Fluid analysis	CLIMATE Moderate
-----------------------	---------------------

PRODUCT RECOMMENDATION 1 SP Gear 1011	PRODUCT RECOMMENDATION 2 Syngear TDL 75W-90	PRODUCT RECOMMENDATION 3 Gearlube GL-5 80W-90
---	---	---

Check every 250 hours

USE Fluid analysis	CLIMATE Cold
-----------------------	-----------------

PRODUCT RECOMMENDATION 1 SP Gear 1081	PRODUCT RECOMMENDATION 2 SP Gear 5015	
---	---	--

Check every 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.