JUNGHEINRICH FORKLIFT TRUCKS, DIESEL DFG DFG 20 BK BX-J PERKINS



704.30 (2001-2003)

ENGINE Perkins 704.30 Capacity: 8 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 40
Check every 50 hours, change every 3 r.	nonths/ 500 hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
Check every 50 hours, change every 3 m	nonths/ 500 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 50 hours, change every 3 r.	nonths/ 500 hours	·

DIFFERENTIAL Capacity: 3,5 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
Check every 3 months/ 500 hours, cl	hange every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 3 months/ 500 hours, cl	hange every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	
Check every 3 months/ 500 hours, ci	hange every 12 months/ 2000 hours	

JUNGHEINRICH FORKLIFT TRUCKS, DIESEL DFG DFG 20 BK BX-J PERKINS



704.30 (2001-2003)

TRANSMISSION Capacity: 12 liter, Capacity: 5 liter (Change capacity)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 20W-20	
Check every 3 months/ 500 hours, change every 12 months/	2000 hours

HYDRAULIC SYSTEM Capacity: 53 liter (Hydraulic tank), Capacity: 58 liter (System)			
USE		CLIMATE	
Normal		Tropical	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
HDX 20W-20	Perlus H 68		

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HDX 10W	Perlus H 46	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

HYDRAULIC BRAKE SYSTEM Capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Charle avant 2 months / FOO hours abo	and avair 12 manths (2000 bavirs	

Check every 3 months/ 500 hours, change every 12 months/ 2000 ho	ours
--	------

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

JUNGHEINRICH FORKLIFT TRUCKS, DIESEL DFG DFG 20 BK BX-J PERKINS



704.30 (2001-2003)

COOLING SYSTEM Capacity: 10,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Charles and EO barres abanda ava	m : 4000 h a : : : : / 40 ma : : : th a	·

Check every 50 hours, change every 1000 hours/ 12 months

REDUCTION UNIT Capacity: 1 liter	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 85W-140	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 3 months/500 hours, change every 12 months/2000 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	

Check every 3 months/500 hours, change every 12 months/2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.