JUNGHEINRICH FORKLIFT TRUCKS, DIESEL DFG DFG 25 BS BX-J PERKINS 704.26 (1999-2004)



ENGINE Perkins 704-26 Capacity: 8 liter					
USE		CLIMATE			
Normal		Tropical			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 40			
Check every 50 hours, change every 3 mo	heck every 50 hours, change every 3 months/ 500 hours				
USE		CLIMATE			
Normal		Mediterranean			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40			
Check every 50 hours, change every 3 mo	nths/ 500 hours				
USE		CLIMATE			
Normal		Cold			
PRODUCT RECOMMENDATION 1					

Multifleet SCD 10W

Check every 50 hours, change every 3 months/ 500 hours

HYDRAULIC SYSTEM Capacity: 53 liter (Hydraulic tank), Capacity: 58 liter (System)				
USE		CLIMATE		
Normal		Tropical		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
HDX 20W-20	Perlus H 68			

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 HDX 10W	PRODUCT RECOMMENDATION 2 Perlus H 46	
-		

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

JUNGHEINRICH FORKLIFT TRUCKS, DIESEL DFG DFG 25 BS BX-J PERKINS 704.26 (1999-2004)



 COOLING SYSTEM

 Capacity: 10,7 liter

 USE
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2
 PRODUCT RECOMMENDATION 3

 Coolant SP 15+
 Coolant SP 12
 Coolant -38 Organic NF

Check every 50 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.