

JUNGHEINRICH FORKLIFT TRUCKS, DIESEL DFG DFG 660 PERKINS 1104D- E44TA (2008-2014)



ENGINE Perkins 1104D-E44TA
Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 10W-40

Check every 50 hours, change every 3 months/ 500 hours

DIFFERENTIAL

Capacity: 9 liter (Single drive wheels), Capacity: 12 liter (Twin drive wheels)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Change every 2000 hours/ 12 months

REDUCTION UNIT

Capacity: 0,9 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Change every 2000 hours/ 12 months

TRANSMISSION 2/2

Capacity: 25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30

Check every 1000 hours, change every 12 months/ 2000 hours

HYDRAULIC SYSTEM

Capacity: 150 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46

PRODUCT RECOMMENDATION 2

Perlus H 46

PRODUCT RECOMMENDATION 3

Perlus HCD 46

Check every 50 hours, change every 12 months/ 2000 hours

JUNGHEINRICH FORKLIFT TRUCKS, DIESEL DFG DFG 660 PERKINS 1104D- E44TA (2008-2014)



GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

COOLING SYSTEM

Capacity: 16 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12

Check every 50 hours, change every 12 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.