JUNGHEINRICH FORKLIFT TRUCKS, ELECTRIC EFG EFG 215 (2004-2008)



HYDRAULIC SYSTEM Capacity: 18 liter				
USE		CLIMATE		
Normal		Tropical		
PRODUCT RECOMMENDATION 1				
Perlus H 68				
Check every 1000 hours, change every 12 months/ 2000 hours				
USE		CLIMATE		
Biodegradable oil		Moderate		
PRODUCT RECOMMENDATION 1				
Perlus Biosynth 46				
Check every 1000 hours, change every 12 months/ 2000 hours				

HYDRAULIC BRAKE SYSTEM Capacity: 0,25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Check every 1000 hours, change ever	y 12 months/ 2000 hours	

GREASE POINTS/NIPPLES

USE

CLIMATE

Normal Moderate

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3

Change every 50 hours

REDUCTION UNIT Capacity: 0,35 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

Check every 1000 hours, change every 12 months/ 2000 hours

JUNGHEINRICH FORKLIFT TRUCKS, ELECTRIC EFG EFG 215 (2004-2008)



WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 1000 hours/ 12 mon	ths	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.