

JUNGHEINRICH FORKLIFT TRUCKS, LPG

TFG TFG 20 BS BH-J GM 3.0 L (2001-2003)



ENGINE GM 3.0 L4
Capacity: 8 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Check every 50 hours, change every 3 months/ 500 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

Check every 50 hours, change every 3 months/ 500 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

Check every 50 hours, change every 3 months/ 500 hours

HYDRAULIC SYSTEM

Capacity: 53 liter (Hydraulic tank), Capacity: 58 liter (System)

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

HDX 20W-20

PRODUCT RECOMMENDATION 2

Perlus H 68

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

HDX 10W

PRODUCT RECOMMENDATION 2

Perlus H 46

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

JUNGHEINRICH FORKLIFT TRUCKS, LPG

TFG TFG 20 BS BH-J GM 3.0 L (2001-2003)

**COOLING SYSTEM**

Capacity: 10,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 15+****PRODUCT RECOMMENDATION 2****Coolant SP 12****PRODUCT RECOMMENDATION 3****Coolant -38 Organic NF**

Check every 50 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.