

## KALMAR SIDELOADING TRUCKS DSA 70 7T

**ENGINE** DSA 70 - Deutz BF4M-1012E

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      |  |
|-------------------------------|-------------------------------|--|
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |  |

*Change every 200 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      |  |
|-------------------------------|-------------------------------|--|
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |  |

*Change every 50 hours*

**DIFFERENTIAL DRIVE AXLE**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1        |  |  |
|---------------------------------|--|--|
| <b>Gearlube HS GL-5 80W-140</b> |  |  |

*Change every 6 months/ 1200 hours*

**HUB REDUCTIONS DRIVE AXLE**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1        |  |  |
|---------------------------------|--|--|
| <b>Gearlube HS GL-5 80W-140</b> |  |  |

*Change every 6 months/ 1200 hours*

**TRANSMISSION** Borg Warner

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Gear Oil Alcat 30</b> |  |  |

*Change every 6 months/ 1200 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |  |
|---------------------------|--------------------------|--|
| <b>Gear Oil Alcat 10W</b> | <b>ATF Dexron II-D</b>   |  |

*Change every 6 months/ 1200 hours*

## KALMAR SIDELOADING TRUCKS DSA 70 7T

**TRANSMISSION** Clark

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Change every 6 months/ 1200 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W**

PRODUCT RECOMMENDATION 2

**ATF Dexron II-D***Change every 6 months/ 1200 hours***TRANSMISSION** Voith

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D***Change every 6 months/ 1200 hours***HYDRAULIC SYSTEM**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Perlus H 32***Change every 6 months/ 1200 hours***GREASE POINTS/NIPPLES**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2****WHEEL BEARINGS**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

# KALMAR SIDELOADING TRUCKS DSA 70 7T



*inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*